

SERIES SD31 Delivers Enhanced Accuracy and Flexible Options



Features and Benefits

Simplified navigation

- Allows user to navigate forwards or backwards from any menu

INFOSENSE™ sensor technology

- Thermal sensing technology improves accuracy by a minimum of 50 percent

Watlow's patented User Defined Menu System

- Allows users to define, save and access their most important Menu settings

WATVIEW HMI (Human Machine Interface)

- Permits operation, configuration and data logging via a standard Windows® PC

Agency approvals

- UL®, C-UL®, CE IP65/NEMA 4X, plus CSA and NSF

Variable burst fire

- Prolongs heater life
- Reduces replacement costs

Fast 6.5Hz Sampling Rate

- Improved control responsiveness

"Save and Restore" feature

- Allows the user to save individual or factory settings

The SERIES SD family of PID temperature controllers utilizes today's advanced micro-electronics technology to provide the value, benefits and accuracy you've come to expect from Watlow. The SERIES SD31 offers improved accuracy of 0.1 percent of span as well as a faster sampling rate of 6.5Hz in a ½ DIN package.

The SERIES SD31 controller delivers many flexible, user-friendly options. Easily choose factory or user defaults and display either process or set point values. Process inputs are scalable and invertible from the front panel. Other features include Variable Burst Fire and flexible Outputs, that users can select as On-Off, Heat/Cool or as Process or Deviation Alarms. Users can also select between 11 different Thermocouples, a 100 Ohm RTD, a 0 to 20mA or 0 to 10V process input - all from the front panel - which eliminates the need for dip-switches.

With optional EIA-485 communications, you can configure, monitor and data log with such optional software products like WATVIEW.

Your Authorized Watlow Distributor Is:



1241 Bundy Boulevard
Winona, Minnesota 55987-5580 USA
Phone: 507-454-5300
Fax: 507-452-4507
Internet: www.watlow.com
e-mail: info@watlow.com

WIN-SD31-0603

ISO 9001



Registered Company
Winona, Minnesota USA

UL® and C-UL® are registered trademarks of Underwriter's Laboratories, Inc.

Modbus™ is a trademark of Schneider Automation, Inc.

Windows® is a registered trademark of Microsoft Corporation

North American Sales Offices: Atlanta, (770)972-4948 • Austin, (512)249-1900 • Birmingham, (205)678-2358 • Charlotte, (704)573-8446 • Chicago, (847)458-1500 • Cincinnati, (513)398-5500 • Cleveland, (330)467-1423 • Dallas, (972)620-6030 • Denver, (303)798-7778 • Detroit, (248)651-0500 • Eastern Canada, (450)433-1309 • Houston, (281)440-3074 • Indianapolis, (317)575-8932 • Kansas City, (913)897-3973 • Los Angeles, (714)935-2999 • Louisiana, (318)864-2864 • Maryland/Virginia, (215)345-8130 • Minneapolis/Manitoba, (952)892-9222 • Nashville, (615)264-6148 • New England, (603)882-1330 • New York/New Jersey/Philadelphia, (215)345-8130 • New York, Upstate, (716)438-0454 • Ontario, (905)979-3507 • Orlando, (407)351-0737 • Phoenix, (602)795-7712 • Pittsburgh, (412)322-5004 • Portland, (503)245-9037 • Raleigh/Greensboro, (336)766-9659 • St. Louis, (314)878-4600 • Sacramento, (707)425-1155 • San Diego, (714)935-2999 • San Francisco, (408)434-1894 • Seattle, (425)222-4090 • Tampa/St. Petersburg, (407)647-9052 • Tulsa, (918)496-2826 • Western Canada, (604)444-4881 • Wisconsin, North (920)993-2161 • Wisconsin, South (262)723-5990

Asian Sales Offices: Australia, +61 (3) 9335-6449 • China, +86 (21) 6277-2138 • Japan, +81 (03) 5403-4688 • Korea, +82 (02) 575-9804 • Malaysia, +60 (4) 641-5977 • Singapore, +65 777-9488 • Taiwan, +886 (0) 7-288-5168

European Sales Offices: France, +33 (01) 3073-2425 • Germany, +49 (0) 7253-9400-0 • Italy, +39 (02) 458-8841 • Sweden, +46 31 7014959 • United Kingdom, +44 (0) 115-964-0777

Latin American Sales Office: Mexico, +52 (442) 217-6235



Specifications

Line Voltage/Power

- 100 to 240V~(ac), +10/-15 percent; (85-264V~[ac]) 50/60Hz, ± 5 percent
- 24V=(ac/dc), +10/-15 percent; 50/60Hz, ± 5 percent
- 10VA maximum power consumption
- Data retention upon power failure via nonvolatile memory

Environment

- -18 to 65°C (0 to 149°F) operating temperature
- -40 to 85°C (-40 to 185°F) storage temperature
- 0 to 90 percent RH, non-condensing

Accuracy

- Calibration accuracy and sensor conformity: ± 0.1 percent of span, $\pm 1^\circ\text{C}$ @ the calibrated ambient temperature and rated line voltage
- Calibration ambient temperature = $25^\circ\text{C} \pm 3^\circ\text{C}$ ($77^\circ\text{F} \pm 5^\circ\text{F}$)
- Accuracy span: 540°C (1000°F) minimum
- Temperature stability: $\pm 0.1^\circ\text{C}/^\circ\text{C}$ ($\pm 0.2^\circ\text{F}/^\circ\text{F}$) rise in ambient maximum

Agency Approvals

- UL® 3121, C-UL®, CSA, CE, IP65/NEMA 4X
- NSF for Type J, K, T and E thermocouples

Controller

- Microprocessor based user-selectable control modes
- Single universal input, up to three outputs
- Control sampling rates: Input = 6.5Hz, Display = 10Hz, Outputs = 6.5Hz

Operator Interface

- Single 4 digit, 7 segment LED displays
- "Set" infinity and up down keys
- Isolated EIA-485 Modbus™ serial communications, 9600, 19.2K or 38.4K baud rates

Wiring Termination -Touch Safe Terminals

- Input power and control outputs 12 to 22 AWG
- Sensor inputs and process outputs 20 to 28 AWG

Universal Input

- Thermocouple, grounded or ungrounded sensors
- RTD 2- or 3-wire, platinum, 100Ω @ 0°C calibration to DIN-curve ($0.00385 \Omega/\Omega^\circ\text{C}$)
- Process, 0-20mA @ 100Ω , or 0-10V=(dc) @ $20k\Omega$ input impedance; Scalable
- Inverse scaling
- $>20M\Omega$ input impedance
- Maximum of 20Ω source resistance

Allowable Operating Range

Type J:	0 to 815°C	or	32 to 1500°F
Type K:	-200 to 1370°C	or	-328 to 2500°F
Type T:	-200 to 400°C	or	-328 to 750°F
Type N:	0 to 1300°C	or	32 to 2372°F
Type E:	-200 to 800°C	or	-328 to 1470°F
Type C:	0 to 2315°C	or	32 to 4200°F
Type D:	0 to 2315°C	or	32 to 4200°F
Type PTII:	0 to 1395°C	or	32 to 2543°F
Type R:	0 to 1760°C	or	32 to 3200°F
Type S:	0 to 1760°C	or	32 to 3200°F
Type B:	0 to 1816°C	or	32 to 3300°F
RTD (DIN):	-200 to 800°C	or	-328 to 1472°F
Process:	-1999 to 9999 units		

Control Outputs

Outputs 1 or 2

- User selectable for heat/cool as on-off, P, PI, PD, PID, or Alarm action
- Electromechanical relay. Form A, rated 2A @ 120V~(ac), 2A @ 240V~(ac) or 2A @ 30V=(dc)
- Switched dc non-isolated minimum turn on voltage of 6V=(dc) into a minimum 500Ω load with a maximum on voltage of not greater than 12V=(dc) into an infinite load. Maximum switched dc power supply current available for up to two outputs is 60mA
- Solid-state relay, Form A, 0.5A @ 24V~(ac) minimum, 264V~(ac) maximum, opto-isolated, without contact suppression
- Process output (Non Isolated) User-selectable 0-10V=(dc), 0-5V=(dc), 1-5V=(dc) @ $1K\Omega$ minimum, 0-20mA, 4-20mA @ 800Ω maximum
- Open collector 42V=(dc) @ 250mA maximum
- EIA-485 serial communications with Modbus™ protocol (output 2 only)
- 9600, 19.2K or 38.4 baud rates

Communications

- Modbus™ EIA-485
- WATVIEW

Dimensions

- $\frac{1}{2}$ DIN size
- 97.8 mm (3.85 in.) behind panel maximum
- Width 52.6 mm (2.07 in.)
- Height 29.7 mm (1.17 in.)

Ordering Information

To order, complete the model number on the right with the information below.

	S D 3 1 -	A - A A
DIN Sizes	_____	_____
3 = $\frac{1}{2}$ DIN		
Control Type	_____	_____
1 = $\frac{1}{2}$ DIN Single Display PID Control		
Power Supply	_____	_____
H = 100 to 240V=(ac/dc)		
L = 24 to 28V=(ac/dc)		
Output 1	_____	_____
C = Switched dc		
K = SSR, Form A, 0.5A		
F = Universal process		
J = Mechanical relay, Form A, 2A		
Output 2	_____	_____
A = None		
C = Switched dc		
K = SSR, Form A, 0.5A		
J = Mechanical relay, Form A, 2A		
U = EIA-485 Modbus™ communications		
Display Colors and Custom Options	_____	_____
OR = Red (Single display units)		
OG = Green (Single display units)		
XX = Custom options, special overlays, etc.		